

10/542500

PATENT

450110-05668

JC20 Rec'd PCT/PTO 1 5 JUL 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Gerfried RANNER et al.  
International Application No.: PCT/EP2004/000316  
International Filing Date: January 16, 2004  
For: SECURE WEB ACCESS VIA AN ORIGINAL CD

745 Fifth Avenue  
New York, NY 10151

EXPRESS MAIL

Mailing Label Number: EV723350468US

Date of Deposit: July 15, 2005

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Charles Jackson  
(Typed or printed name of person mailing paper or fee)

Charles Jackson  
(Signature of person mailing paper or fee)

CLAIM OF PRIORITY UNDER 37 C.F.R. § 1.78(a)(2)

Mail Stop PCT  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

Pursuant to 35 U.S.C. 119, this application is entitled to a claim of priority to European Application No. 03001030.0 filed on January 17, 2003.

Respectfully submitted,

FROMMER LAWRENCE & HAUG LLP  
Attorneys for Applicants

By: William S. Frommer  
William S. Frommer  
Reg. No. 25,506  
Tel. (212) 588-0800

Best Available Copy



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

Rec'd BGT/EP200 4/ 0 0 0 3 1 6  
PCT/PTO 15 JUL 2005

10/542500

RECEIVED

18 MAR 2004

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03001030.0

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk



Anmeldung Nr:  
Application no.: 03001030.0  
Demande no:

Anmeldetag:  
Date of filing: 17.01.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Sony DADC Austria AG  
Sonystasse 20  
5081 Anif  
AUTRICHE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Secure WEB access via an original CD

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

G11B20/00

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT SE SI SK TR LI

**HOEFER SCHMITZ WEBER & PARTNER**

EPO-Munich  
58

**17. Jan. 2003**

**Attorney's File: SON030101PEP**

**Gö**

**Applicant's Case: S03P5001EP00/PAE03-001DADC**

**17.01.2003**

**Sony DADC Austria AG**

**Sonystrasse 20**

**A-5081 Anif**

**Austria**

---

**Secure WEB Access via an Original CD**

---

17. Jan. 2003

## Description

The present invention relates to a method for securing an access to a predetermined area of a target server, a method for starting a secure access to a predetermined area of a target server, and a record carrier.

To achieve a better position in the market and to better satisfy customers, today's CD and/or DVD labels, i.e. producers, want to offer added value and bonus material (in the following only referred to as bonus material) to a CD content and/or DVD content to the customers. A convenient way is to offer such services via the internet. However, such a system to offer bonus material must be secured to legitimate buyers of a respective record carrier, which might also include CD-ROMs or other current or future record carriers.

Therefore, currently secure internet connections that can be accessed with key-codes are offered to customers to access such bonus material. The key-codes are generally serialized e.g. on the data set and have to be entered during a login procedure on a login page to enter predetermined protected areas. The applicant's European patent application 02 003 465.8 "Method and Device for supplying of a Data Set stored in a Database", filed on February 14, 2002, which content is herewith included into this application, describes such a system. The disadvantage of such a method is that the key-codes can be shared and the user experience/convenience suffers.

Therefore, it is the object underlying the present invention to provide an improved system to offer bonus material to a legitimate customer of a record carrier.

According to the present invention, this object is solved by a method for securing an access to a predetermined area of a target server as defined in independent claim 1, a method for starting a secure access to a predetermined area of a target server as defined in independent claim 5, and a record carrier as defined in independent claim 20. Preferred embodiments of the methods and record carrier according to the present invention are defined in the respective dependent claims. A computer program product according to the present invention is defined in claim 18 and a computer readable storage means is defined in claim 19.

The method for securing an access to a predetermined area of a target server according to the present invention comprises the step of providing an information file on a copy protected record carrier, which information file  
5 comprises a project identifier and/or an address of an authentication server with which an application using said information file can communicate so that the authentication server can initiate and confirm a connection between a computer on which said application is started and said predetermined area of said target server that is identified by the authentication server and/or the  
10 project identifier.

Further, the method for starting a secure access to a predetermined area of a target server according to the present invention comprises the step of accessing  
of an information file on a copy protected record carrier, which information file  
15 comprises a project identifier and/or an address of an authentication server with which an application using said information file can communicate so that the authentication server can initiate and confirm a connection between a computer on which said application is started and said predetermined area of said target server that is identified by the authentication server and/or the  
20 project identifier.

Finally, the record carrier according to the present invention is copy protected and comprises an information file, which comprises a project identifier and/or an address of an authentication server with which an application using said  
25 information file can communicate so that the authentication server can initiate and confirm a connection between a computer on which said application file is started and a predetermined area of a target server that is identified by the authentication server and/or the project identifier.

Therefore, according to the present invention the record carrier, e.g. a compact or digital versatile disc with audio and/or video information, comprises an information file, e.g. in a second session, and is copy protected by a generally known or future copy protection, e.g. the today used SecuROM copy protection, as described in the applicants European Patent EP 0 899 733 B1, which content  
30 is herewith included by reference. This guarantees that an application that accesses this file, or the information file as said application, can distinguish an original record carrier from a copy. With the data comprised in the information file the user can securely access the predetermined area on the target server that  
35

is preferably an internet server, e.g. the bonus material on a content server of the disc label. Since the data is provided in an executable file or accessible to an executable file, i.e. as an or within an application, that can access an automatic client/server authentication system preferably in a secure manner to grant  
5 access to certain target servers, e.g. websites, or areas, it can be secured that no key-codes, URLs etc. can be shared with others, since an access is only possible with the original record carrier in the disc drive. Further, the user experience/convenience is very good, since no complicated interaction, such as the typing of long serial codes, is necessary, but the access can be easily  
10 initiated, e.g. by a mouse-click. Preferably, the application opens the standard Web browser of the user/computer with the address of the authentication server and transmits at least the project identifier. The security level is quite high, i.e. as high as the security level of the copy protection.

15 The application might be provided on the record carrier, and/or on a server, preferably downloadable, and/or on an access-software record carrier, i.e. so that a user can start the execution of the application on the computer. In case the application is provided on the record carrier itself, the information file might be a part of the application and/or the application consist of only the  
20 information file that is in this case executable.

The information file comprises the project identifier and/or the address of the authentication server. This information is included according to the used authentication system. E.g. in case only one authentication server exists, the  
25 address of the authentication server needs not to be included in the information file on the record carrier, since it can be hard coded in the application that e.g. can be downloaded from a server of the disc label. On the other hand, in case one authentication server exists for every different project, e.g. different CD content, no project identifier needs to be included in the information file, since  
30 the address of the respective authentication server alone indicates the predetermined area on the target server. In this case the target server, i.e. content server, and the authentication server might be one physical device that might include further target and/or authentication servers. Of course, in case different authentication servers exist that are designed for authentication of  
35 different projects, e.g. one for each disc label that handles all different discs of that label, the respective address of the authentication server and the project identifier have to be included in the information file.

According to the present invention preferably an autorun-information file is provided on said record carrier, which autorun-information file provides an automatic execution of a predetermined executable file after the record carrier is loaded in a reading device.

According to the present invention preferably an autostart file is provided on said record carrier, which autostart file gets automatically executed after the record carrier is placed and loaded in a reading device and which autostart file provides a link to start said application, or which autostart file is part of said application, or which autostart file is said information file.

According to the present invention preferably the application gets started from said record carrier, or from a server, preferably as a download, or via an access-software record carrier, preferably after an installation of the application on a hard disc of the computer.

According to the present invention, preferably said application verifies whether or not the record carrier is an original and performs said communication with said authentication server in case of a positive verification.

According to the present invention preferably said executable file transmits a changing parameter of the computer, in particular a randomly generated number and/or a computer system time to said authentication server.

According to the present invention, additionally or alternatively preferably said authentication server verifies whether or not the communication with said application and/or a transmission of said project identifier as a request for a connection between said computer and said predetermined area of said target server is posted from said application and initiates a connection of said computer with said predetermined area of said target server in case of a positive verification. This verification might be performed on basis of an encryption/decryption scheme used to secure the information that is communicated between the application and the authentication server or parts thereof.

According to the present invention, said authentication server further additionally or alternatively preferably verifies whether or not a changing



parameter of the computer, in particular a randomly generated number and/or a computer system time transmitted from said computer, was not already previously used and initiates a connection of said computer with said predetermined area of said target server in case of a positive verification.

5

According to the present invention, preferably after a positive verification a connection between said authentication server and said target server is set-up by said authentication server that connects to said target server to secure that the computer is connected to said predetermined area of said target server via said authentication server.

10

According to the present invention, in this case, preferably

- the authentication server generates a session identifier based on the positive verified values and transmits said session identifier to said target server via said connection between said authentication server and said target server,
- said connection between said computer on which said application is started and said predetermined area of said target server is set up by redirecting the connection between the computer and the authentication server to the target server or by forwarding data of the protected area to the computer, and
- said connection between said computer on which said application is started and said predetermined area of said target server is executed after the target server received a confirmation of a validity of the session identifier from the authentication server. The forwarding of data of the protected area to the computer might include that data needed to establish a connection between the computer and the target server is forwarded so that such a connection might be set-up from the computer side or that data that the computer user requests, e.g. contents of the target server, are forwarded, i.e. the computer only communicates with the authentication server that communicates with the target server.

15

20

25

According to the present invention the validity of the session identifier is preferably confirmed by the authentication server by positively determining whether or not the session identifier exists and/or whether or not the session identifier was already requested to be valid.

30

According to the present invention the target server preferably assigns a temporary session cookie to the computer so that the whole predetermined area of the target server can be accessed via said connection between said computer on which said application is started and said target server

35

According to the present invention preferably said record carrier is copy protected by copy protecting the information file.

5

According to the present invention preferably said predetermined area on said target server comprises bonus material of the content that is included on the record carrier besides said executable file, e.g. a video to a song included on the record carrier.

10

According to the present invention preferably said information file is a part of said application or is an executable file of said application.

15

The computer program product according to the present invention comprises computer program means adapted to perform the method steps as set-out above or parts thereof when being executed on a computer, digital signal processor, or the like.

20

The computer readable storage means according to the present invention comprises a computer program product according to the present invention.

25

All different aspects of the present invention as set-out above and further elucidated below might be combined in any way. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate an embodiment of the invention and, together with a general description of the invention given above, and the detailed description of the embodiment given below, serve to explain the principles of the invention, wherein:

30

**Fig. 1** shows an embodiment of an environment to offer bonus material and added value according to the present invention,

**Fig. 2** shows a functionality description of the embodiment shown in Fig. 1, and

**Fig 3** shows a flow chart of the authentication server and the target server according to an embodiment of the present invention.

35

The environment to offer bonus material and added value as shown in Fig. 1 allows to restrict the access to predetermined areas and services offered on a website to only owners of a particular, copy protected record carrier, e.g. CD 1.

Copy CDs 7 of the original CD1 will not provide the access, since the copy might not be accessible e.g. in case of a copy protection of the whole CD, or the executable file that provides the access according to the present invention which is provided on the original CD 1 is not copied due to a copy protection of this file, or original and duplicate are distinguishable due to their behaviour and the environment offers the bonus material only to originals, i.e. generally since the executable file or the whole CD 1 is copy protected. Therefore, only a buyer of the original CD 1 has access to bonus material, such as video streams, music downloads, games, price reductions in online shops, and so on.

Once the user has inserted the original CD 1 into a computer 2, an access of a portal 3 that offers the bonus material and/or the additional services is possible e.g. via the internet 4. The shown portal 3 offers an authentication 3a after which bonus material 3b, push services 3c, and mobile services 3d are available.

Further, community services 3e, customer relationship 3f, and games/chat 3h are offered as well as an information window 3g. Via the portal 3 the verified user can access media rich content from an online digital production library 5 and can communicate via a MM-Message Service Centre 6 with a wireless network. The bonus material 3b, community services 3e, customer relationship 3f, and games/chat 3h might be internet services, the push services 3c might be directed to the internet, e.g. e-mail, or to mobile phones or smartphones, e.g. short message service. The mobile services 3d might be directed to mobile phones or smartphones.

The added value offered to the customer, i.e. the owner of the copy protected CD 1 according to the present invention, is protected intellectual property of the artists and publishers, e.g. music or video publishers, since tethered services are only available through the original record carrier. Further, the convenience and quality expected is provided which is a prerequisite to keep consumers away from p2p networks. Also, the tracking of user behaviour is possible so that one2one relationships, i.e. profiles, might be build up. The portal 3 might also serve as an extended platform for marketing activities and it bridges the gap between physical/electronic and mobile content delivery. The portal 3 might further show a build in DRM functionality for the major software players, such as the Real & Windows Media Player, which offers a convergence of media, e.g. CD/internet/mobile devices. An individual feedback according to a listing of preferences is possible and the community aspect might be satisfied by offering chats, games and downloads.

Fig. 2 shows an overview of the functionality of the environment shown in Fig. 1. The CD 1 comprises a SecuROM copy protected executable file, which secures that a user that executes the file is the legitimate owner of the CD 1. The executable file is the executable information file as set-out above, i.e. combines the executable file of the application and the information file. The executable file opens the standard browser 8 of the user with the address of the authentication server 9. At least a project identifier that corresponds to the predetermined area that comprises the bonus material etc. is also communicated to the authentication server 9, since in this case one authentication server handles several projects. Preferably, also a computer identifier is transmitted to the authentication server 9 to automatically identify a user.

The authentication server 9 verifies whether the request that is posted by addressing the authentication server 9 and communicating the project identifier is posted by the executable file and in case of a positive verification redirects the browser to the target address that corresponds to the target area so that the portal 3 of the target server or predetermined area of the target server is displayed. The authentication server 9 determines the target address from the project identifier. While redirecting the browser, the authentication server 9 communicates with the target server or predetermined area of the target server to secure that the user accesses the services via the authentication server 9.

The original record carrier, here the CD 1, might not only comprise the normal content, e.g. audio and/or video, and the executable file that provides the address of the authentication server and the project identifier, but also a file "autorun.inf" and a file "start.exe". The file autorun.inf secures an automatic loading of the file start.exe after the record carrier is placed and loaded in the drive and the file start.exe is an application that generates a preferably graphical user interface, which offers different possibilities of services related to the record carrier such as bibliography, games, etc. and a link to the executable file according to the present invention that provides the address of the authentication server and the project identifier, i.e. that initiates and executes the connection to the secured content.

In a preferred embodiment of the present invention said executable file generates a unique 8 byte computer identifier from the serial number and volume name of

the hard disc "C", the checksum of the computer name, and the version of the operating system.

The executable file then opens the standard browser of the user and transmits e.g. the computer identifier, the project identifier and the system time to the authentication server 9 via the query string of the URL of the authentication server 9. This data is preferably key-coded. An example would be:

<http://auth.sonydadc.com/auth.go?id=0B2C67B84A8B2C67B84A013FE2013FE2D676E6...>

The project identifier is hard coded in the executable file, which means that a new executable file must be generated for every project, e.g. different CD. The authentication server 9 verifies and stores the data as follows:

- decoding of the data string,
- verification whether the string was used already, if this is the case then denying the access,
- comparing the system time from the data string with the system times already previously obtained from the user (on basis of the computer identifier), if the new system time is bigger then granting the access, otherwise denying the access,
- generating of a 16 bit session identifier for this access, and
- redirecting the user to the target page, i.e. target area, of the target server, wherein the session identifier is communicated as query string.

The right hand side of Fig. 3 shows the communication between the authentication server 9 and the target server to access a secured web page as entry point of said predetermined area of the target server. As described above, in a first step S1 the user gets redirected after the positive authentication to the target server, e.g. a content server of the disc label, to the layout start of the protected page. With the redirecting also the session identifier generated by the authentication server 9 gets communicated to the target server via the query string. Therefore, such a redirecting could be:

<http://www.shakira.com/bonus.php?id=KS1757SKD6K9JGAWE...>

After it is determined in a following second step S2 that no user session is active, the target server waits for a call from the authentication server 9 in a third step S3 and after the call the protected page directs a request to the authentication server 9 whether or not the session identifier is valid in a fourth step S4 in which the authentication server 9 also communicates a handshake protocol to the target server. The authentication server 9 determines for this verification whether or not the validity of the session identifier was requested earlier, i.e. whether or not the session identifier is still usable, and whether or not the session identifier exists at all. In case no call from the authentication server comes in the third step S3, the target server stops the access. The target server determines in a following fifth step S5 whether or not a communication with the authentication server is executed and in case of a valid authentication server 9 verifies whether or not the user might have access to the protected page in a sixth step S6. In case no valid authentication server communicates with the target server in the fifth step S5, the target server stops the access. In case it is determined in the sixth step S6 that the user might have access, the user session is started in an eighth step S8, otherwise a communication between target server and authentication server 9 is performed in a seventh step S7 to newly log-in the user.

After the user session is started in the eighth step S8 or it is determined in the second step S2 that a user session is already active, the access to the content is given in a following ninth step S9, so that the user might access the whole predetermined area without new authentication. Thereafter the layout of the protected page ends in a tenth step S10.

For comparison, the left hand side of Fig. 3 shows a normal page that has its content directly between the layout start and the layout end.

The executable file according to the present invention that provides the preferably automated access to the authentication server with at least the project identifier allows to easily modify the contents of a web server so that they are only accessible via the execution of the executable file.

To properly perform its functionality, the authentication server might comprise several tables in a database model. One table might store the core data of each project. Among other things, there are stored a project identifier, the hash of this project identifier and the URL where the browser should be linked or

5 redirected to. A further table might store each request from the executable file  
according to the present invention so that a request can be verified, since no  
duplicates are allowed, and also for billing purposes. Among other things there  
are stored the project identifier, the computer identifier, an automatically  
created numeric counterpart of the computer identifier and an automatically  
created random session identifier string. Another table might be written from  
the target server side via an interface. This table protocols the accesses to the  
protected content, also within a session. The usage of this table is optional. It is  
necessary in case the number of accesses of one user/computer should be  
10 limited to a predetermined amount and no database should be provided on the  
target server side.

## Claims

EPO-Munich  
58

17. Jan. 2003

1. Method for securing an access to a predetermined area of a target server, characterized by providing an information file on a copy protected record carrier, which information file comprises a project identifier and/or an address of an authentication server with which an application using said information file can communicate so that the authentication server can initiate and confirm a connection between a computer on which said application is started and said predetermined area of said target server that is identified by the authentication server and/or the project identifier.

2. Method according to anyone of the preceding claims, characterized by providing an autorun-information file on said record carrier, which autorun-information file provides an automatic execution of a predetermined executable file after the record carrier is loaded in a reading device.

3. Method according to anyone of the preceding claims, characterized by providing an autostart file on said record carrier, which autostart file gets automatically executed after the record carrier is placed and loaded in a reading device and which autostart file provides a link to start said application, or which autostart file is part of said application, or which autostart file is said information file.

4. Method according to anyone of the preceding claims, characterized by providing the application on said record carrier, or on a server, preferably downloadable, or on an access-software record carrier.

5. Method for starting a secure access to a predetermined area of a target server, characterized by accessing of an information file on a copy protected record carrier, which information file comprises a project identifier and/or an address of an authentication server with which an application using said information file can communicate so that the authentication server can initiate and confirm a connection between a computer on which said application is started and said predetermined area of said target server that is identified by the authentication server and/or the project identifier.



6. Method according to claim 5, **characterized by** starting the application from said record carrier, or from a server, preferably as a download, or via an access-software record carrier, preferably after an installation of the application on a hard disc of the computer.

7. Method according to anyone of the preceding claims, **characterized in that** said application verifies whether or not the record carrier is an original and performs said communication with said authentication server in case of a positive verification.

8. Method according to anyone of the preceding claims, **characterized in that** said application transmits a changing parameter of the computer, in particular a randomly generated number and/or a computer system time to said authentication server.

9. Method according to anyone of the preceding claims, **characterized in that** said authentication server verifies whether or not the communication with said application and/or a transmission of said project identifier as a request for a connection between said computer and said predetermined area of said target server is posted from said application and initiates a connection of said computer with said predetermined area of said target server in case of a positive verification.

10. Method according to anyone of the preceding claims, **characterized in that** said authentication server verifies whether or not a changing parameter of the computer, in particular a randomly generated number and/or a computer system time transmitted from said computer, was not already previously used and initiates a connection of said computer with said predetermined area of said target server in case of a positive verification.

11. Method according to claim 9 or 10, **characterized in that** after a positive verification a connection between said authentication server and said target server is set-up by said authentication server that connects to said target server to secure that the computer is connected to said predetermined area of said target server via said authentication server.

12. Method according to claim 11, **characterized in that**

- the authentication server generates a session identifier based on the positive verified values and transmits said session identifier to said target server via said connection between said authentication server and said target server,

5 - said connection between said computer on which said application is started and said predetermined area of said target server is set up by redirecting the connection between the computer and the authentication server to the target server or by forwarding data of the protected area to the computer, and

10 - said connection between said computer on which said application is started and said predetermined area of said target server is executed after the target server received a confirmation of a validity of the session identifier from the authentication server.

13. Method according to claim 12, **characterized in that**

15 - the authentication server confirms the validity of the session identifier by positively determining whether or not the session identifier exists and/or whether or not the session identifier was already requested to be valid.

14. Method according to claim 12 or 13, **characterized in that**

20 - the target server assigns a temporary session cookie to the computer so that the whole predetermined area of the target server can be accessed via said connection between said computer on which said application is started and said target server.

25 15. Method according to anyone of the preceding claims, **characterized in that** said record carrier is copy protected by copy protecting the information file.

30 16. Method according to anyone of the preceding claims, **characterized in that** said predetermined area on said target server comprises bonus material of the content that is included on the record carrier besides said executable file.

17. Method according to anyone of the preceding claims, **characterized in that** said information file is a part of said application or is an executable file of said application.

35 18. Computer program product, comprising computer program means adapted to perform the method steps as defined in anyone of claims 1 to 17 or

parts thereof when being executed on a computer, digital signal processor, or the like.

19. Computer readable storage means, comprising a computer program  
5 product according to claim 18.

20. Record carrier, **characterized by** being copy protected and comprising an  
information file, which comprises a project identifier and/or an address of an  
authentication server with which an application using said information file can  
10 communicate so that the authentication server can initiate and confirm a  
connection between a computer on which said application file is started and a  
predetermined area of a target server that is identified by the authentication  
server and/or the project identifier.

21. Record carrier according to claim 20, **characterized in that** said  
15 application verifies whether or not the record carrier is an original and performs  
said communication with said authentication server in case of a positive  
verification.

22. Record carrier according to anyone of the preceding claims, 20 to 21  
20 **characterized in that** said application transmits a changing parameter of the  
computer, in particular a randomly generated number and/or a computer system  
time to said authentication server.

23. Record carrier according to anyone of the preceding claims 20 to 22,  
25 **characterized in that** said record carrier is copy protected by copy protecting  
the information file.

24. Record carrier according to anyone of the preceding claims 20 to 23,  
30 **characterized by** an autorun-information file, which provides an automatic  
execution of a predetermined executable file after the record carrier is loaded in  
a reading device.

25. Record carrier according to anyone of the preceding claims 20 to 24,  
35 **characterized by** an autostart file, which gets automatically executed after the  
record carrier is placed and loaded in a reading device and which autostart file  
provides a link to start said application, or which autostart file is part of said  
application, or which autostart file is said information file.

26. Record carrier according to anyone of the preceding claims 20 to 25, **characterized by** comprising the application.

5 27. Record carrier according to anyone of the preceding claims 20 to 26, **characterized in that** said information file is a part of said application or is an executable file of said application.

10 28. Record carrier according to anyone of the preceding claims 20 to 27, **characterized in that** said predetermined area on said target server comprises bonus material of the content that is included on the record carrier besides said information file.

**Abstract**EPO-Munich  
58**Secure WEB Access via an Original CD****17. Jan. 2003**

- 5 A system for securing an access to a predetermined area of a target server uses a copy protected record carrier comprising an information file, which comprises a project identifier and/or an address of an authentication server with which an application using said information file can communicate so that the authentication server can initiate and confirm a connection between a computer
- 10 on which said application is started and said predetermined area of said target server that is identified by the authentication server and/or the project identifier.

(Fig. 2)




Fig. 1






Fig. 2



Content Page without protection



Protected page

Fig. 3



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☒ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**